



TYPICAL SECTION

NTS

NOTES:

1. 6" FINISH SOIL LAYER SHALL COMPLY WITH SECTION 162 OF FDOT STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION, 2004 EDITION.
2. REMOVE UNSUITABLE MATERIAL (EXISTING PAVEMENTS, ROADWAY BASE, LIMEROCK, MILLINGS AND OTHER DEBRIS), TO A MINIMUM DEPTH OF 4'-0" BELOW FINISHED GRADE IN MEDIAN AREAS. MEDIAN FILL SOIL, FOR AREAS THAT ARE EXCAVATED, SHALL BE NATIVE SITE SOILS APPROVED BY THE ENGINEER. IN THE ABSENCE OF SUFFICIENT NATIVE SITE SOILS, REPLACEMENT FILL SHALL BE SUITABLE FOR PLANT GROWTH AND APPROVED BY THE ENGINEER. EXCAVATION AND REPLACEMENT SOIL SHALL BE INCLUDED IN PAY ITEM FOR "EXCAVATION OF UNSUITABLE MATERIAL"
3. DO NOT DISTURB EXISTING MEDIAN SOILS EXCEPT TO REMOVE EXISTING UNSUITABLE MATERIALS LISTED IN NOTE NO. 2, OR TO CONSTRUCT PROPOSED IMPROVEMENTS.

DEPARTMENT OF PUBLIC WORKS			
PINELLAS COUNTY, FLORIDA			
MEDIAN SOIL; COMPOSITION AND DEPTH			
APPROVED BY:	DATE	SHEET	INDEX
<i>[Signature]</i> DIRECTOR OF PUBLIC WORKS	3/05	1 of 1	1105