



**NOTE:**

1. ADJUST SIDEWALK TO AVOID OBSTRUCTIONS, AS SHOWN, OR AS DIRECTED BY THE ENGINEER, IN ACCORDANCE WITH FDOT MANUAL OF UNIFORM MINIMUM STANDARDS FOR DESIGN, CONSTRUCTION, AND MAINTENANCE FOR STREETS AND HIGHWAYS – LATEST EDITION ("FLORIDA GREEN BOOK").
2. CONSTRUCTION OF SIDEWALKS SHALL MEET ADA REQUIREMENTS AS SPECIFIED IN FDOT INDEX NOS. 515 AND 304.
3. POWER POLES SHALL BE MOVED WHEN POSSIBLE.
4. TREES SHALL BE TRIMMED TO MAINTAIN VERTICAL CLEARANCE: 9 FT. FOR SIDEWALKS AND 18 FT. FOR ROADS.
- \*5. MAXIMUM LATERAL DEFLECTION SHALL BE 5:1.
6. REMOVE TREE ROOTS WITHIN 10" OF PROPOSED GRADE.
7. CONTRACTION JOINTS SHALL MEET FDOT INDEX No. 310.
8. APPLY DETAIL TO ACCOMMODATE M.H. CONFLICTS. COVERS TO BE REPLACED AS REQUIRED TO MAINTAIN FLUSH SURFACE AND PATTERN.

**PLAN VIEW**

DEPARTMENT OF PUBLIC WORKS PINELLAS COUNTY, FLORIDA			
<b>GUIDELINES FOR SIDEWALK ALIGNMENT</b>			
APPROVED BY:	DATE	SHEET	INDEX
<i>[Signature]</i> DIRECTOR OF PUBLIC WORKS	7/09	1 of 1	1357