

PINELLAS COUNTY FLEET VEHICLE PARTNERSHIP SOLICITATION

**Issued By:
Front Row Marketing Services
on behalf of
Pinellas County**

**Submittal Date:
March 24, 2006 3:00pm
Mr. Chris K. Baker/
Mr. John P. McDonald
Front Row Marketing Services L.P.
780 94th Ave. N., Suite 107
St. Petersburg, FL 33802
727-456-1161**

TABLE OF CONTENTS

SECTION I - GENERAL INFORMATION

1.1	OBJECTIVE	3
1.2	PROPOSAL REQUIREMENTS	3
1.3	EVALUATION CRITERIA	4
1.4	PERIOD OF CONTRACT	4
1.5	EXCLUSIVITY	4
1.6	NON-MANDATORY PRE-SALES SOLICITATION CONFERENCE	4
1.7	PROPOSAL SUBMITTAL COPIES	4
1.8	TIMELINE	5

SECTION II – SCOPE OF WORK

2.1	BACKGROUND INFORMATION	6
2.2	FLEET VEHICLE PROJECTIONS & SPECIFICATIONS	6
2.3	SPONSORSHIP OPPORTUNITIES	7

SECTION III – EVALUATION CRITERIA

3.1	COMPANY PROFILE	9
3.2	PROPOSAL SUBMISSION FORMS	10

ATTACHMENTS

FLEET VEHICLE PROJECTIONS & SPECIFICATIONS	13
--	----

SECTION I - GENERAL INFORMATION

1. OBJECTIVE:

Front Row Marketing, on behalf of Pinellas County, is seeking qualified vehicle dealership(s) to enter into a mutually beneficial partnership with the County to engage in a Countywide Fleet Vehicle Sponsorship Program. Both domestic and import vehicles will be considered. What is a Fleet Vehicle Sponsorship Program?

A Fleet Vehicle Sponsorship Program is a newer concept in municipalities and has been extremely successful for the dealership(s) and other municipalities. It is a concept where the County enters into a long-term business relationship with the dealership(s). The County has a need for vehicles and cost reduction while your dealership has a need for business and marketing your dealership(s), brands, services and products throughout the region.

Pinellas County will be awarding an exclusive contract to a dealership(s) that will provide the County the most advantageous partnership. Over the next three years the County will be purchasing approximately 70 vehicles annually. With this partnership, the County purchases vehicles for a minimum of three years directly through your dealership(s). The County also will provide unique and valuable marketing opportunities for your products, brands, and services within the County's determined advertising/ sponsorship properties. In exchange for these advertising rights, the dealership(s) provide the County with an investment of sponsorship dollars, in-kind trade, and marketing support.

2. PROPOSAL REQUIREMENTS:

Each proposal should contain the following at a minimum. Proposer must also address detailed requirements as specified in Section II, Scope of Work.

- a. A written narrative describing your vehicle brands, and company marketing initiatives on a local, regional and national level.
- b. A description of your experience in providing fleet vehicles to other public or private entities.
- c. The specifications of each proposed vehicle as compared with the specifications, as outlined in Section II, Scope of Work, for the corresponding vehicle type. Minimum vehicle warranty and recommended preventive maintenance schedule shall all be included.
- d. The costs for each vehicle type as outlined in Section II, Scope of Work.
- e. The sponsorship revenues, in-kind trade and marketing programs that will be received by the County.

3. EVALUATION CRITERIA:

This contract will be awarded to the most qualified Proposer, per the evaluation criteria listed in Section III.

4. PERIOD OF CONTRACT:

The Proposer shall provide desired period of contract, and it must be for a minimum of three years.

5. EXCLUSIVITY:

The County is offering to the successful firm(s) the following rights, if applicable: the exclusive rights to become the Official Vehicle/Auto Dealership Provider(s) of Pinellas County.

6. NON-MANDATORY PRE-SALES SOLICITATION CONFERENCE:

There will be a **non-mandatory** pre-sales solicitation conference on **March 9 @ 2:00 p.m. to be held at Front Row Marketing Services, 780 94th Avenue North, Suite 107 St. Petersburg, FL 33702.**

All questions pertaining to the sales solicitation or technical specifications will be reviewed at this time. Proposal suggestions or modifications may be discussed with County representatives and consultants at this meeting and may be considered by representatives as possible addenda to the sales solicitation.

7. PROPOSAL SUBMITTAL COPIES:

Proposals shall be submitted in one (1) original and five (5) copies with the 'Original' clearly marked.

8. TIMELINE:

Following is a listing of actions and anticipated dates; the County reserves the right to change the dates, if necessary.

Date	
February 23, 2006	Advertising & Publishing Solicitation
March 9, 2006 @ 2:00 p.m.	Sales Solicitation Non-Mandatory Conference Front Row Marketing Services office 780 94 th Avenue N., Suite 107 St. Petersburg, FL 33702
March 16, 2006	Deadline for Questions/Clarifications
March 24, 2006	Proposals due at Front Row Marketing Services office by 3:00 p.m.
March 27 through April 21, 2006	Evaluation of the Sales Solicitation and/or Negotiations
April 24, 2006	Recommendation due
May 16, 2006	Submit recommendation to Board for Award of Contract

SECTION II – SCOPE OF WORK

1. BACKGROUND INFORMATION

The County currently purchases vehicles either through a competitive bid process or in accordance with the State of Florida Purchasing Contract. The objective of this solicitation is for the County to obtain one or multiple dealership(s) who will be awarded this solicitation exclusively in which the winning Proposer(s) will receive the County Fleet Vehicle Business for the vehicle types specified in this solicitation (Approximately seventy (70) vehicles are purchased annually) for a minimum of three years. Subsequently the winning Proposer(s) will enter into a sponsorship agreement where the County will receive sponsorship dollars, in-kind trade, and advertising/marketing programs on behalf of the dealership(s)/brands. The dealership(s) will be allowed to market goods and services throughout the County with pre-approved sponsorship opportunities working with County Staff and the County's Sponsorship Consultant. Some potential opportunities are listed in Section II.3 below. The dealership(s) will work directly with the consultant in defining and enhancing all possible opportunities and are encouraged to be creative in their responses.

* Both domestic and import vehicles will be considered. Please note that this solicitation does not represent the Pinellas County Sheriff or the Pinellas County Schools.

2. FLEET VEHICLE PROJECTIONS & SPECIFICATIONS

Find attached a summary of vehicles that are projected to be purchased by Pinellas County for the next three years. This list should be submitted as a part of your proposal, with the proposed pricing. *Note that this list is subject to change. If applicable, feel free to make recommendations regarding other vehicles that are environmentally friendly.

3. SPONSORSHIP OPPORTUNITIES

Pinellas County boasts a population of over 927,000 and the County attracts more than 16 million visitors to the finest parks and beaches in North America. Fort De Soto Park was recently named the #1 Beach in America. There are many unique sponsorship programs the County has to offer that will allow for a dealership(s) brand and/or national brands to be recognized in front of a unique demographic in Pinellas County to support a dealership's marketing efforts locally, regionally, and nationally. Dealership(s) brands and products will receive recognition as being associated with Pinellas County, FL and also showcased throughout the County. The County is open to any and all opportunities that will generate awareness for a dealership's brand(s) in the County.

In your proposal, please address your proposed plan for the following three items:

- a.) Sponsorship Dollars allocated to the County on behalf of your Brand/Dealership(s)
- b.) In-Kind Trade (Vehicles donated to the County in exchange for advertising rights)
- c.) Proposed Marketing Programs to help Promote County Parks, Programs, and Events

The County is open to being creative and establishing marketing/advertising partnerships that are mutually beneficial to the awarded Proposer. Other opportunities can be discussed during negotiations and proposers are encouraged to be creative when proposing marketing/advertising elements they would like to receive.

Find below a list of *potential* marketing/advertising opportunities the County can provide the awarded Proposer. This list is not intended to be comprehensive and additional ideas will be considered:

- a) Ability to 'wrap' vehicles with your trademarks/logo in highly visible locations such as Fort De Soto Park, Sand Key Park and Fred Howard Park.
- b) Awarded Proposer will be designated as the 'Official' Auto Dealership of Pinellas County and will be able to create a public relations plan announcing this to the residents and visitors of the County.
- c) Potential sponsorship opportunities of County community programs and special events.
- d) Ability to offer special discounts to Pinellas County employees, retirees, and family members for vehicles, leases, and maintenance that the general public cannot receive.
- e) Call to action marketing collateral stuffers in Utility bills.
- f) Ability to have temporary car displays showcased in the County.
- g) The fleet of vehicles purchased through the dealership may all have name recognition on the vehicle of the area dealership.
- h) Right to film commercials, television shows on Pinellas County property with no facility rental/use fee (with approval/availability).
- i) Right to use County rental/picnic areas with no facility rental/use fee (Time and Space to be Mutually agreed upon).
- j) Pinellas County will provide the right to allow the winning bidder the use of County logos in statements reflecting its sponsorship status in advertising and promotional materials.
- k) Prominently display winning bidder's signage, vehicles and/or logos at all County sponsored beach activities.
- l) Official partner status on County Website Sponsorship Homepage
<http://www.pinellascounty.org/sponsor>

Please see below a few examples of what other automobile companies have done in the past in conjunction with municipalities:

- a) The City of San Diego, CA struck a deal with McCune Chrysler-Jeep where McCune provides the City with 16 Vehicles to be utilized by the San Diego Lifeguard beach patrol fleet. The City benefits directly through a reduction in the number of vehicles they must purchase and McCune Chrysler-Jeep benefits by gaining increased name-brand recognition through logo displays on Lifeguard patrol vehicles, exclusive rights to promote a special employee purchase program to City employees, retirees and their families and a presence on the City's award-winning website.
- b) Huntington Beach, CA struck a deal with Nissan where Nissan provided the County 20 vehicles for use in the City's Marine Safety, Beach Maintenance, and Park/Camping Operations, and also cash to support a summer concert series. In exchange, Nissan receives exposure and recognition on these vehicles, at special events, and was designated 'official' vehicle status.
- c) Los Angeles County, CA struck a deal with Nissan that granted the County 65 lifeguard vehicles to offset capital costs. In exchange for the vehicles, Nissan receives advertising exclusivity on all the beaches.
- d) Pinellas County, FL School Board has adopted a sponsorship program within their own fleet of vehicles, where they received vehicle donations from a local area dealership in 2002.
- e) At Temple University, the Athletic Department engaged in a fleet vehicle relationship with Volkswagen. Volkswagen receives signage and promotions at Athletic events, while all coaches receive their own Volkswagen vehicle to use. Volkswagen is also designated as the 'Official' Import Vehicle of Temple Athletics.
- f) The Kansas City Brigade, an Arena Football League Team is allowed the use of three SUV Vehicles for the 2006 Season. In exchange for the SUV's, Albright Chevrolet-Pontiac-GMC receives use of a suite, television commercials and a sign in the arena for all home games.

SECTION III – EVALUATION CRITERIA

Front Row Marketing Services staff will evaluate the proposals and develop a list of proposers to interview on the basis of criteria including, but not limited to, the following:

- a.) Pricing
- b.) Proposer's Qualifications
- c.) Vehicle Specifications
- d.) Company Profile
- e.) Sponsorships
- f.) Proposal Requirements

Please also address the following questions below regarding your company's profile.

1. **COMPANY PROFILE:**

- a. Provide a brief history of your organization and an executive summary that describes your company's qualifications. This summary shall include number of employees and number of years in business.
- b. Indicate any parent or subsidiary relationships with other businesses.
- c. List your corporate office organizational structure and direct contact with County should you be awarded the contract.
- d. List all contracts your company, related companies or subcontractors have had with Pinellas County or its related agencies in the last five years.
- e. List any experiences in the last five years in which you, your company or related companies and/or subcontractor failed to successfully complete a contract. List any contractual arrangements, which were canceled or not renewed for poor performance.
- f. Provide a list of customer references (at least three [3]) to whom your firm has provided Fleet Vehicles, preferably with a similar government entity.
- g. Provide the name, address and telephone number of your customer contact responsible for each account. At the discretion of Pinellas County, these persons may be contacted as references by the selection committee.
- h. Provide any reason and background information as to any potential conflict that may exist that would have any negative effect on a formal working relationship between Proposer and County.
- i. Provide a list of current sponsorship programs and community programs that your company engages in throughout Pinellas County.

2. **PROPOSAL SUBMISSION FORMS:**

All proposals shall be signed in ink by authorized principals of the firm.

Proposals are to be submitted in a sealed envelope. The face of the envelope shall indicate the name and address of the firm, and title of the proposal.

Proposals are to be submitted to Front Row Marketing Services L.P., 780 94th Ave. N., Suite 107, St. Petersburg, FL 33702, by the date and time indicated on the cover sheet.

Proposals shall be submitted in one (1) original and five (5) copies.

VENDOR NAME: _____

VENDOR ADDRESS: _____

TELEPHONE: _____

FAX: _____

EMAIL ADDRESS: _____

*** REQUIRED ENTRY – ACCOUNT REP**

EMAIL ADDRESS: _____

*** REQUIRED FOR ELECTRONIC NOTIFICATIONS**

I hereby agree to abide by all conditions of this solicitation and certify that I am authorized to sign this proposal for the Proposer.

AUTHORIZED SIGNATURE: _____

NAME & TITLE (print): _____

**PLEASE ACKNOWLEDGE RECEIPT OF ADDENDA FOR THIS SOLICITATION BY
SIGNING AND DATING BELOW:**

ADDENDUM NO.	SIGNATURE/PRINTED NAME	DATE RECEIVED

Note: Prior to submitting the response to this solicitation, it is the responsibility of the firm submitting a response to confirm if any addenda have been issued. If such document(s) has been issued, acknowledge receipt by signature and date in section above. Failure to do so may result in being considered non-responsive or result in lowering the rating of a firm's proposal.

Information regarding Addenda issued is available on the Purchasing Department section of the County's website at, www.pinellascounty.org/purchase, listed under category 'Bid Schedule'.

NOTE: If you do not intend to submit a proposal on this requirement, please return this form immediately.

Thank you.

Front Row Marketing Services
780 94th Avenue N., Suite 107
St. Petersburg, FL 33702

We, the undersigned have declined to submit a proposal

- ☐ Specifications too "tight", i.e., geared toward one brand or manufacturer only (explain below).
- ☐ Insufficient time to respond to the solicitation.
- ☐ We do not offer this product or service.
- ☐ Our schedule would not permit us to perform.
- ☐ Unable to meet specifications.
- ☐ Specifications unclear (explain below).
- ☐ Other (specify below).

COMPANY NAME: _____

DATE: _____

SIGNATURE: _____

TYPED NAME OF ABOVE: _____

TELEPHONE: _____

FAX: _____

EMAIL: _____

ATTACHMENTS

FLEET VEHICLE PROJECTIONS & SPECIFICATIONS

Total	Rplc. Class Description	Next Replace Year
15	SEDAN, INTERMEDIATE	2006
1	TRUCK, COMPACT PU EXT CAB 4X2	2006
10	TRUCK, 1/2 TN, PICKUP	2006
8	TRUCK, 1/2 TN, PU W/EXT CAB	2006
2	TRUCK, 3/4 TN, PU REGULAR CAB 4X2	2006
2	TRUCK, 3/4 TN, PU EXT CAB 4X2	2006
10	TRUCK, 3/4 TN, PU EXT CAB 4X4	2006
10	UTILITY VEHICLE, ECON, 4 DR, 4X4	2006
3	UTILITY VEHICLE, ECON, 4 DR, 4X2	2006
4	CARGO MINI VAN	2006
5	VAN 1/2 TN, CARGO	2006
8	PASSENGER MINI VAN	2006
2	3/4 TON CARGO VAN	2006
1	VAN, 1 TON, 5 PASSENGER	2006
6	TRUCK, 1TN. CREWCAB, W/UTILITY BODY	2006

Total	Rplc. Class Description	Next Replace Year
2	SEDAN, COMPACT	2007
5	SEDAN, INTERMEDIATE	2007
1	TRUCK, COMPACT PU EXT CAB 4X2	2007
6	TRUCK, 1/2 TN, PICKUP	2007
2	TRUCK, 1/2 TN, PU W/EXT CAB	2007
2	TRUCK, 1/2 TN, PICKUP 4X4	2007
4	TRUCK, 3/4 TN, PU REGULAR CAB 4X2	2007
5	TRUCK, 3/4 TN, PICKUP 4x4	2007
12	UTILITY VEHICLE, ECON, 4 DR, 4X4	2007
1	PASSENGER MINI VAN	2007
5	3/4 TON CARGO VAN	2007
3	TRUCK 1 TN. CREWCAB PICKUP	2007

Total	Rplc. Class Description	Next Replace Year
7	SEDAN, INTERMEDIATE	2008
5	TRUCK, 1/2 TN, PICKUP	2008
1	TRUCK, 1/2 TN, PICKUP 4X4	2008
7	TRUCK, 1/2 TN, PU W/EXT CAB	2008
3	TRUCK, 1/2 TN, PU W/EXT CAB 4X4	2008
3	TRUCK, 3/4 TN, PU REGULAR CAB 4X2	2008
6	TRUCK, 3/4 TN, PICKUP 4x4	2008
5	UTILITY VEHICLE, ECON, 4 DR, 4X2	2008
13	UTILITY VEHICLE, ECON, 4 DR, 4X4	2008
3	CARGO MINI VAN	2008
7	PASSENGER MINI VAN	2008
3	3/4 TON CARGO VAN	2008
1	VAN, 1 TON, 12-15 PASSENGER	2008
4	TRUCK 1 TN. CREWCAB PICKUP	2008
6	TRUCK, 1TN. CREWCAB, W/UTILITY BODY	2008

GENERAL MINIMUM SUGGESTED SPECIFICATIONS

Automobile, Intermediate, Five (5) Passenger, Four (4)-Door Sedan
Chevrolet Malibu, Ford 500, Dodge Stratus, Hybrid Equivalent or Pinellas County Approved
Equal

G.V.W.:

- N/A

C.A./W.B.:

- 106.3 W.B. minimum in wheel base

ENGINE:

- Minimum six (6) cylinder gasoline with 200 horsepower and 220 ft/lbs torque @ 4000 RPM
- Multi-port fuel injection

COOLING SYSTEM:

- Heaviest available cooling system package with coolant recovery system.
- Cooling system shall be filled with extended life coolant with freeze protection to -30 degrees F, or approved equal.

ALTERNATOR:

- Alternator shall be a 105 AMP minimum
- Battery shall be a minimum of 525 CCA

TRANSMISSION:

- Electronic 4 speed with overdrive
- Transaxle

STEERING:

- Power

BRAKES:

- Power, 4 wheel antilock
- 4 wheel disc brakes

SPRINGS:

- Manufacturer's standard

AXLES:

- Manufacturer's standard

WHEELS AND TIRES:

- 15" steel wheels with P205/65R-15 tires

BODY:

- Standard Four (4) door sedan

FUEL TANK:

- Minimum 12 gallon

WINDSHIELD WIPERS:

- Intermittent with washer

CAB AND MISCELLANEOUS:

- Unit to contain all standard equipment including:
- Factory heater and defroster
- Factory air conditioner
- AM/FM radio
- Interior dome light
- Cigarette lighter
- Tinted glass on rear windows
- Daytime running lamps
- No fleet-delete packages to be applied.
- Trunk or cargo area to contain OEM mat or carpeting
- Cloth upholstery required on all seats
- Fold-in mirrors on left and right sides
- Matching floor mats

COLOR:

- Exterior - white
- Interior - Tan

KEYS:

- Three (3) full sets required

SHOP MANUALS:

- Three full sets of repair and troubleshooting manuals

GENERAL MINIMUM SUGGESTED SPECIFICATIONS

Pickup Truck, Compact Extenda-cab 4x2

Chevrolet Colorado, Ford Ranger, Dodge Dakota, or County Approved Equivalent

G.V.W.:

- 5,000 lb. Minimum
- 4,000 lb towing capacity minimum

C.A./W.B.:

- 125.9 in. minimum

ENGINE:

- Minimum six (6)-cylinder gasoline with 220 h.p. and 225 ft.lbs. torque @ 2800

COOLING SYSTEM:

- Heaviest available cooling system package with coolant recovery system.
- Cooling system shall be filled with extended life coolant with freeze protection to -30 degrees F, or approved equal.

ALTERNATOR:

- Alternator shall be a 105 AMP minimum
- Battery shall be a minimum of 600 CCA

STEERING:

- Power

BRAKES:

- 4 wheel disc brakes
- Power 4 wheel antilock

TRANSMISSION:

- 4 speed automatic with electronically controlled overdrive

SPRINGS:

- Front: 2,35 lbs minimum
- Rear: 2,755 lbs minimum

AXLES:

- Front: 2,533 lbs minimum
- Rear Axle – 2,896 lbs minimum
- Limited slip differential
- 3.73 ratio

WHEELS & TIRES:

- Five (5) matching 15" x 6" steel wheels
- P205/75R15 tires with highway tread design.

FUEL TANK:

- Standard

BUMPERS & HOOKS:

- Standard front bumper
- Heavy duty rear bumper with receiver hitch, frame mounted w/combo pintle hitch & 2" ball.
- 6 pole female trailer plug
 - Model Pollock #11-609 or approved equal

BODY:

- Four door
- 72.7 inch inside length at floor fleetside bed with double wall construction

WINDSHIELD WIPERS:

- Intermittent

CAB & MISCELLANEOUS:

- Extended - cab with all manufacturer's standard equipment.
- Truck to feature:
- Factory heater/defroster
- Factory air conditioner
- AM/FM radio
- Interior dome light with reading lamps
- Cigarette lighter
- Day/night rear mirrors
- Fold away mirrors on left and right side
- Heavy duty three (3) man cloth bench seat for front, no rear seat
- Tinted glass all around
- Daytime running lamps
- Matching floor mats

COLOR:

- Exterior – white
- Interior – Tan

KEYS:

- Three (3) full sets required

SHOP MANUALS:

- Three full sets of repair and troubleshooting manuals

GENERAL MINIMUM SUGGESTED SPECIFICATIONS

Pickup Truck, 1/2 Ton, Full-Size 4x4

Ford F150, GMC Sierra K1500, Chevrolet K1500 or County Approved Equivalent

G.V.W.:

- 6,400 lb. Minimum
- 8,100 lb towing capacity

C.A./W.B.:

- 133 in. wheelbase minimum

ENGINE:

- Minimum V-8 cylinder gasoline with 285 HP and 295 ft./lbs torque @ 4,000 RPM

COOLING SYSTEM:

- Heaviest available cooling system package with coolant recovery system.
- Cooling system shall be filled with extended life coolant with freeze protection to -30 degrees F, or approved equal.

ALTERNATOR:

- Alternator shall be a 145 AMP
- Battery shall be a minimum of 600 CCA.

TRANSMISSION:

- Electronically controlled 4-speed automatic overdrive w/tow pkg.
- Electronic transfer case with push-button controls
- Factory OEM skid plates on transmission and transfer case.

STEERING:

- Power

BRAKES:

- Power 4 wheel antilock
- 4 wheel disc brakes

SPRINGS:

- Front: 3,925 lbs minimum
- Rear: 3,750 lbs minimum

AXLES:

- Designed to meet G.V.W.
- Rear axle to be of limited slip design
- 3.73 ratio

WHEELS/TIRES:

- Five (5) 17" x 7" 6-lug steel, painted, includes painted center caps standard wheels with five (5) matching P265/70R17, all-season, blackwall having an on road/off road tread design.
- Spare to be mounted inside or underneath chassis.

BODY:

- 8 ft. fleetside bed with double wall construction.
- Bedliner

BUMPERS:

- Standard front bumper with tow hooks mounted on frame.
- Heavy duty rear step bumper with receiver style hitch frame mounted with combo pintle & 2" ball
- 6 pole female trailer plug
 - Model Polock #11-609 or approved equal

FUEL TANK:

- 30-gallon minimum single tank.

WINDSHIELD WIPERS:

- Intermittent

CAB & MISCELLANEOUS:

- Standard cab with all manufacturer's standard equipment
- Factory air conditioning,
- Factory heater and defroster
- Tinted glass
- Cloth bench seat
- AM/FM radio
- Fold-in mirrors right & left side
- Inside day/night rear view mirror
- Cigarette lighter
- Power point in dash
- Interior dome light.
- Daytime running lamps
- Floor mats (2)

KEYS:

- Three (3) full sets required

COLOR:

- White exterior
- Tan interior

SHOP MANUALS:

- Three full sets of repair and troubleshooting manuals

GENERAL MINIMUM SUGGESTED SPECIFICATIONS

Pickup Truck, 1/2 Ton, Full-Size Extendacab 4x4
Ford F150, GMC Sierra K1500, Chevrolet K1500 or County Approved Equivalent

G.V.W.:

- 6,400 lb. Minimum
- 7,700 lb towing capacity

C.A./W.B.:

- 157.5 in. wheelbase minimum

ENGINE:

- Minimum V-8 cylinder gasoline with 285 HP and 295 ft./lbs torque @ 4,000 RPM

COOLING SYSTEM:

- Heaviest available cooling system package with coolant recovery system.
- Cooling system shall be filled with extended life coolant with freeze protection to -30 degrees F, or approved equal.

ALTERNATOR:

- Alternator shall be a 145 AMP
- Battery shall be a minimum of 600 CCA.

TRANSMISSION:

- Electronically controlled 4-speed automatic overdrive w/tow pkg.
- Electronic transfer case with push-button controls
- Factory OEM skid plates on transmission and transfer case.

STEERING:

- Power

BRAKES:

- Power 4 wheel antilock
- 4 wheel disc brakes

SPRINGS:

- Front: 3,925 lbs minimum
- Rear: 3,750 lbs minimum

AXLES:

- Designed to meet G.V.W.
- Rear axle to be of limited slip design
- 3.73 ratio

WHEELS/TIRES:

- Five (5) 17" x 7" 6-lug steel, painted, includes painted center caps standard wheels with five (5) matching P265/70R17, all-season, blackwall having an on road/off road tread design.
- Spare to be mounted inside or underneath chassis.

BODY:

- 4 door with 8 ft. fleetside bed with double wall construction.
- Bedliner

BUMPERS:

- Standard front bumper with tow hooks mounted on frame.
- Heavy duty rear step bumper with receiver style hitch frame mounted with combo pintle & 2" ball
- 6 pole female trailer plug
 - Model Pollock #11-609 or approved equal

FUEL TANK:

- 30-gallon minimum single tank.

WINDSHIELD WIPERS:

- Intermittent

CAB & MISCELLANEOUS:

- Standard cab with all manufacturer's standard equipment
- Factory air conditioning,
- Factory heater and defroster
- Tinted glass
- Cloth bench seat, no rear seat
- AM/FM radio
- Fold-in mirrors right & left side
- Inside day/night rear view mirror
- Cigarette lighter
- Power point in dash
- Interior dome light.
- Daytime running lamps
- Floor mats (2)

KEYS:

- Three (3) full sets required

COLOR:

- White exterior
- Tan interior

SHOP MANUALS:

- Three full sets of repair and troubleshooting manuals

GENERAL MINIMUM SUGGESTED SPECIFICATIONS

Pickup Truck, 3/4 Ton, Full-Size 4x2

Ford F250, GMC Sierra 2500, Chevrolet C2500 or County Approved Equivalent

G.V.W.:

- 9,200 lb. Minimum
- 10,500 lb towing capacity minimum

C.A./W.B.:

- 133 in. wheelbase minimum

ENGINE:

- Minimum V-8 gasoline with 300 HP with 360 ft.lbs torque @ 4,000 RPM

COOLING SYSTEM:

- Heaviest available cooling system package with coolant recovery system.
- Cooling system shall be filled with extended life coolant with freeze protection to -30 degrees F, or approved equal.

ALTERNATOR:

- Alternator shall be a 105 AMP minimum
- Battery shall be a minimum of 600 CCA.

TRANSMISSION:

- Electronically controlled 4-speed automatic overdrive w/tow pkg.

STEERING:

- Power

BRAKES:

- Power 4 wheel antilock
- 4 wheel disc brakes

SPRINGS:

- Front: 4,500 lbs minimum
- Rear: 6,000 lbs minimum

AXLES:

- Designed to meet G.V.W.
- Rear axle to be of limited slip design
- 3.73 ratio

WHEELS/TIRES:

- Five (5) 16" x6.5" 6-lug steel, painted, includes painted center caps standard wheels with five (5) matching P245/70R16, all-season, blackwall having a highway tread design.
- Spare to be mounted inside or underneath chassis.

BODY:

- 8 ft. fleetside bed with double wall construction.

BUMPERS:

- Standard front bumper with tow hooks mounted on frame.
- Recessed step bumper on rear
- Receiver style hitch w/combo pintle & 2" ball
- 6 pole female trailer plug
 - Model Polock #11-609 or approved equal

FUEL TANK:

- Standard dual tanks, or 30-gallon minimum single tank.

WINDSHIELD WIPERS:

- Intermittent

CAB & MISCELLANEOUS:

- Standard cab with all manufacturer's standard equipment
- Factory air conditioning,
- Factory heater and defroster
- Tinted glass
- Cloth bench seat
- AM/FM radio
- Fold-in mirrors on right and left side
- Inside day/night rear view mirror
- Power point in dash
- Interior dome light.
- Daytime running lamps
- Floor mats

KEYS:

- Three (3) full sets required

COLOR:

- Exterior - White
- Interior - tan

SHOP MANUALS:

- Three full sets of repair and troubleshooting manuals

GENERAL MINIMUM SUGGESTED SPECIFICATIONS

Pickup Truck, 3/4 Ton, Full-Size with Extenda-cab 4x2
Ford F250, GMC Sierra 2500, Chevrolet C2500 or County Approved Equivalent

G.V.W.:

- 9,200 lb. Minimum
- 10,200 lb towing capacity minimum

C.A./W.B.:

- 157.5 in. wheelbase minimum

ENGINE:

- Minimum V-8 gasoline with 300 HP with 360 ft.lbs torque @ 4,000 RPM

COOLING SYSTEM:

- Heaviest available cooling system package with coolant recovery system.
- Cooling system shall be filled with extended life coolant with freeze protection to -30 degrees F, or approved equal.

ALTERNATOR:

- Alternator shall be a 105 AMP minimum
- Battery shall be a minimum of 600 CCA.

TRANSMISSION:

- Electronically controlled 4-speed automatic overdrive w/tow pkg.

STEERING:

- Power

BRAKES:

- Power 4 wheel antilock
- 4 wheel disc brakes

SPRINGS:

- Front: 4,500 lbs minimum
- Rear: 6,000 lbs minimum

AXLES:

- Designed to meet G.V.W..
- Rear axle to be of limited slip design
- 3.73 ratio

WHEELS/TIRES:

- Five (5) 16" x6.5" 6-lug steel, painted, includes painted center caps standard wheels with five (5) matching P245/70R16, all-season, blackwall having a highway tread design.
- Spare to be mounted inside or underneath chassis.

BODY:

- Four (4) doors and 8 ft. fleetside bed with double wall construction.

BUMPERS:

- Standard front bumper with tow hooks mounted on frame.
- Recessed step bumper on rear
- Receiver style hitch w/combo pintle & 2" ball
- 6 pole female trailer plug
 - Model Pollock #11-609 or approved equal

FUEL TANK:

- Standard dual tanks, or 30-gallon minimum single tank.

WINDSHIELD WIPERS:

- Intermittent

CAB & MISCELLANEOUS:

- Four (4) door Extendacab with all manufacturer's standard equipment
- Factory air conditioning,
- Factory heater and defroster
- Tinted glass
- Cloth bench seat, no rear seat
- AM/FM radio
- Fold-in mirrors on right and left side
- Inside day/night rear view mirror
- Power point in dash
- Interior dome light.
- Daytime running lamps
- Floor mats

KEYS:

- Three (3) full sets required

COLOR:

- Exterior - White
- Interior - tan

SHOP MANUALS:

- Three full sets of repair and troubleshooting manuals

GENERAL MINIMUM SUGGESTED SPECIFICATIONS

Sport Utility Vehicle (SUV), 4 Door, 4X4, Gasoline
GMC Envoy, Chevrolet Trailblazer, Ford Explorer or County Approved Equivalent

G.V.W.:

- 5,700 lb. Minimum
- Towing capacity of 5,200 lbs minimum

C.A./W.B.:

- 113 in. wheelbase minimum

ENGINE:

- Minimum six (6) cylinder gasoline with 290 HP and 275 ft.lbs torque @ 3600 RPM

COOLING SYSTEM:

- Heaviest available cooling system package with coolant recovery system.
- Cooling system shall be filled with extended life coolant with freeze protection to -30 degrees F, or approved equal.

ALTERNATOR:

- Shall be a 150 AMP alternator minimum
- Battery shall be a minimum of 600 CCA.

TRANSMISSION:

- Electronically controlled 4-speed automatic overdrive w/tow pkg.
- Electronically controlled 2-speed transfer case.
- Factory OEM skid plates on transmission and transfer case.

STEERING:

- Power

BRAKES:

- Power 4 wheel antilock
- 4 wheel disc brakes

SPRINGS:

- Front: 3,100 lbs minimum
- Rear: 3,200 lbs minimum

AXLES:

- Designed to meet G.V.W..
- Rear axle to be of limited slip design
- Front axle to possess automatic locking hubs
- 3.73 ratio

WHEELS/TIRES:

- Five (5) standard wheels with five (5) matching P235/70R16 tires having an on road/off road tread design.
- Spare to be mounted inside or underneath chassis.

BODY:

- Standard four (4) door, five (5) passenger

BUMPERS:

- Standard front bumper with tow hooks mounted on frame.
- Heavy duty rear bumper with receiver style hitch frame mounted with combo pintle & 2"ball.
- 6 pole female trailer plug
 - Model Polock #11-609 or approved equal

FUEL TANK:

- Standard with steel protector shield 18 gallons min.

WINDSHIELD WIPERS:

- Intermittent electric

CAB AND MISCELLANEOUS:

- Unit to contain all standard factory equipment including
- Factory air conditioning,
- Factory heater and defroster
- Tinted glass
- Cloth interior
- AM/FM radio
- Fold-in mirrors on left and right sides
- Inside day/night rear view mirror
- Cigarette lighter
- Power point in dash
- Interior dome light.
- Trunk or cargo area to contain OEM mat.
- Daytime running lamps
- Matching floor mats

KEYS:

- Three (3) full sets required

COLOR:

- White exterior
- Tan interior

SHOP MANUALS:

- Three full sets of repair and troubleshooting manuals

GENERAL MINIMUM SUGGESTED SPECIFICATIONS

Sport Utility Vehicle SUV, 4 door 4X2

GMC Envoy, Chevrolet Trailblazer, Ford Explorer or County Approved Equivalent

G.V.W.:

- 5,500 lb. Minimum
- Towing capacity of 5,300 lbs minimum

C.A./W.B.:

- 113 in. wheelbase minimum

ENGINE:

- Minimum six (6) cylinder gasoline with 290 HP and 275 ft.lbs torque @ 3600 RPM

COOLING SYSTEM:

- Heaviest available cooling system package with coolant recovery system.
- Cooling system shall be filled with extended life coolant with freeze protection to -30 degrees F, or approved equal.

ALTERNATOR:

- Alternator shall be a 150 AMP minimum
- Battery shall be a minimum of 600 CCA.

TRANSMISSION:

- Electronically controlled 4-speed automatic overdrive w/tow pkg.

STEERING:

- Power

BRAKES:

- Power 4 wheel antilock
- 4 wheel disc brakes

SPRINGS:

- Front: 3,100 lbs minimum
- Rear: 3,200 lbs minimum

AXLES:

- Designed to meet G.V.W.
- Rear axle to be of limited slip design
- 3.73 ratio

WHEELS/TIRES:

- Five (5) standard wheels with five (5) matching P235/70R16 tires with a highway tread design.
- Spare to be mounted inside or underneath chassis.

BODY:

- Standard four (4) door, five (5) passenger

BUMPERS:

- Standard front bumper.
- Heavy duty rear bumper with a category class 3 receiver hitch, frame mounted w/combo pintle hitch & 2"ball.
- 6 pole female trailer plug
 - Model Polock #11-609 or approved equal

FUEL TANK:

- Standard with steel protector shield 18 gallons min.

WINDSHIELD WIPERS:

- Intermittent electric

CAB AND MISCELLANEOUS:

- Unit to contain all standard factory equipment including factory air conditioning,
- Factory heater and defroster
- Tinted glass
- Cloth interior
- AM/FM radio
- Fold-in mirrors on left and right sides
- Inside day/night rear view mirror
- Cigarette lighter
- Power point in dash
- Interior dome light.
- Trunk or cargo area to contain OEM mat.
- Daytime running lamps
- Matching floor mats

KEYS:

- Three (3) full sets required

COLOR:

- White exterior
- Tan interior

SHOP MANUALS:

- Three full sets of repair and troubleshooting manuals

GENERAL MINIMUM SUGGESTED SPECIFICATIONS

Van, Mini Cargo 2 Passenger

Chevrolet Uplander, Ford Freestar, Dodge Caravan or County Approved Equivalent

G.V.W.:

- 5,600 minimum

C.A./W.B.:

- 121 in. wheelbase

ENGINE:

- Minimum six (6) cylinder gasoline with 200 HP and 220 ft. lbs. torque@ 4,400 RPM

COOLING SYSTEM:

- Heaviest available cooling system package with coolant recovery system.
- Cooling system shall be filled with extended life coolant with freeze protection to -30 degrees F, or approved equal.

ALTERNATOR:

- Alternator shall be a 140 AMP minimum
- Battery shall be a minimum of 600 CCA

TRANSMISSION:

- Electronic 4 speed with overdrive
- Transaxle

STEERING:

- Power

BRAKES:

- Power 4 wheel ABS
- 4 wheel disc brakes

SPRINGS:

- Heavy duty to meet G.V.W.

AXLES:

- To meet G.V.W.

WHEELS/TIRES:

- Five (5) matching tires and wheels, P225/60R17, with spare mounted under chassis.
- 17 x 6.5 steel wheels

BODY:

- Standard cargo van body with dual rear doors and sliding cargo doors on right and left side.
- Glass in side and rear doors only.
- General service shelving package

BUMPERS:

- Standard front bumper
- Standard rear bumper

WINDSHIELD WIPERS:

- Intermittent

CAB AND MISCELLANEOUS:

- All manufacturer's standard equipment
- Factory heater/defroster
- Factory air conditioner
- AM/FM radio
- Cigarette lighter
- Fold-in right & left mirrors
- Cloth driver and passenger seats with arm rests and seat belts
- Interior dome lights in both cab area and in cargo area.
- All glass in van is to be tinted
- The van must contain OEM rubber flooring in cab and full headliner
- Daytime running lamps
- Floor mats (2).

COLOR:

- Exterior - white
- Interior - tan

KEYS:

- Three (3) complete sets required

SHOP MANUALS:

- Three full sets of repair and troubleshooting manuals

GENERAL MINIMUM SUGGESTED SPECIFICATIONS

Van, Mini Cargo 8 Passenger

Dodge Caravan, Ford Windstar, Chevrolet Uplander or County Approved Equivalent

G.V.W.:

- N/A

C.A./W.B.:

- 113 in. wheelbase

ENGINE:

- Minimum six (6) cylinder gasoline with 200 HP and 220 ft./ lbs. Torque @4,400 RPM

COOLING SYSTEM:

- Heaviest available cooling system package with coolant recovery system.
- Cooling system shall be filled with extended life coolant with freeze protection to -30 degrees F, or approved equal.

ALTERNATOR:

- Alternator shall be a 140 AMP minimum
- Battery shall be a minimum of 600 CCA

TRANSMISSION:

- Electronic 4 speed with overdrive

STEERING:

- Power

BRAKES:

- Power 4 wheel ABS
- 4 wheel disc brakes

SPRINGS:

- Heavy duty to meet G.V.W.

AXLES:

- Front: To meet G.V.W.
- Rear: To meet G.V.W.

WHEELS/TIRES:

- Five (5) matching tires and wheels, 225/60R17, with spare mounted under chassis.
- 17 x 6.5 steel wheels

BODY:

- Standard van body, with dual rear doors or swing up rear doors, sliding side door passenger and driver side
- Seating for eight (8) passengers, and glass in all panels.

BUMPERS:

- Standard front and rear bumper

WINDSHIELD WIPERS:

- Intermittent

CAB AND MISCELLANEOUS:

- All manufacturer's standard equipment
- Factory heater/defroster
- Dual factory air conditioner
- AM/FM radio
- Cigarette lighter
- Fold-in mirrors right & left side
- Cloth seats. Driver's and front passenger seats to have arm rests
- Interior dome lights in both cab area and in cargo area.
- All glass in van is to be tinted
- Carpeting in van
- Daytime running lamps.
- Matching floor mats

COLOR:

- Exterior - white
- Interior - Tan

KEYS:

- Three (3) complete sets required

SHOP MANUALS:

- Three full sets of repair and troubleshooting manuals

GENERAL MINIMUM SUGGESTED SPECIFICATIONS

Van, Cargo, 3/4 Ton, Gasoline, 2 Passenger 4x2

GMC Savana 2500, Ford E250, Chevrolet Express 2500 or County Approved Equivalent

G.V.W.:

- 8,600 lb. Minimum

C.A./W.B.:

- 135 in. wheelbase

ENGINE:

- Minimum V-8 gasoline with 285 h.p. and 295 ft./lbs torque @ 4,000 RPM

COOLING SYSTEM:

- Heaviest available cooling system package with coolant recovery system.
- Cooling system shall be filled with extended life coolant with freeze protection to -30 degrees F, or approved equal.

ALTERNATOR:

- Alternator shall be a 105 AMP minimum
- Battery shall be a minimum of 600 CCA.

TRANSMISSION:

- 4 speed automatic, electronically controlled with overdrive.

STEERING:

- Power

BRAKES:

- Power 4 wheel antilock
- 4 wheel disc brakes

SPRINGS:

- Front - independent coil springs and stabilizer bar
- Rear - rear multi-leaf springs to meet GVW

AXLES:

- Front: To meet G.V.W.
- Rear: To be limited slip
- 3.73 ratio

WHEELS & TIRES:

- Five (5) 16" x 6.5" 6-lug steel, painted, includes painted center caps standard wheels with five (5) matching P235/75R16EL, all-season, blackwall having a highway tread design.
- Spare to be mounted underneath chassis.

BODY:

- Standard cargo van body with dual rear doors and sliding cargo door on the right side.
- Glass in side and rear doors only.
- General service shelving package

BUMPERS:

- Standard front bumper with tow hooks mounted on frame.
- Rear: Recessed step.

CAB & MISCELLANEOUS:

- All manufacturer's standard equipment
- Factory heater/defroster
- Factory air conditioning
- AM/FM radio
- Cigarette lighter
- Fold-in mirrors on right and left side
- Cloth driver and passenger seat with arm rests
- Interior dome lights in cab area and in rear cargo area
- Full headliner
- Daytime running lamps
- All glass in the van is to be tinted
- Floor to have rubber mat full length of cargo area
- Floor mats

COLOR:

- White exterior
- Tan interior

KEYS:

- Three (3) full sets required

SHOP MANUALS:

- Three full sets of repair and troubleshooting manuals

GENERAL MINIMUM SUGGESTED SPECIFICATIONS

Truck, 1 Ton, Six (6) Passenger Crew –Cab 4x2 Full-Size w/ Dual Rear Wheels & Utility Body
Chevrolet C3500, Ford F-350 Super Duty Series, or County Approved Equivalent

G.V.W.:

- 11,400 lb. Minimum
- Towing capacity of 12,000 lbs minimum

C.A./W.B.:

- 167 “ wheelbase

ENGINE:

- Minimum Diesel V-8 with 310 horsepower and 605 ft/lbs torque @ 1,600 RPM

COOLING SYSTEM:

- Heaviest available cooling system package with coolant recovery system.
- Cooling system shall be filled with extended life coolant with freeze protection to –30 degrees F, or approved equal.

ALTERNATOR:

- Alternator shall be a 105 AMP minimum
- Shall be dual batteries with a minimum of 770 CCA each.

TRANSMISSION:

- 4-speed automatic overdrive w/tow pkg.

STEERING:

- Power

BRAKES:

- Power 4 wheel antilock
- 4 wheel disc brakes

SPRINGS:

- Front – 4,800 lbs minimum
- Rear – 8,600 lbs minimum

AXLES:

- Front: to meet G.V.W.
- Rear: Rear to be limited slip
- 3.73 gear ratio

WHEELS/TIRES:

- Seven (7) matching tires LT-215/85Rx16, tubeless radials, with highway tread appropriate for GVW rating.
- 16 x 6.5 steel wheels, dual rear wheels.

BODY:

- Knapheide 7108DFB - or equal. 49 inch floor width low profile utility body
- Compartments at least 19-inch deep and flip top tool bins.

- Factory installed lights in all bins.
- Factory installed bar locks for all compartments.
- Body supplied must possess all lights and reflectors as required by applicable Federal and State regulations.
- All tail/stop lights will be recessed in the utility body.
- The utility body must be square, and constructed from Galvanneal steel.
- All body panels, shelves and doors must be free from sharp burrs.
- All welds must be dressed.
- All doors will have hollow automotive type compression gaskets, foam gaskets are not acceptable
- Body must be painted with base coat / clear coat to match the cab color.
- The completed body must have no rust upon delivery, nor display any rusting of undamaged surfaces for a period of forty five (45) days following delivery to the County.
- **NO FABRICATED BODIES WILL BE ACCEPTED.**
- Pre-wired from the factory.
- All connections shall be soldered with heat shrink covering. Stainless latches and aluminum fuel cup.
- Recess step bumper.

BUMPERS:

- Standard front bumper with tow hooks mounted on frame.
- Recessed step bumper on rear
- Receiver style hitch w/combo pintle & 2" ball
- 6 pole female trailer plug
 - Model Pollock #11-609 or approved equal

FUEL TANK:

- 30-gallon minimum capacity. The fuel tank(s) must not interfere with the storage capacity of the truck bed and have a protective shield.

WINDSHIELD WIPERS:

- Intermittent electric

CAB AND MISCELLANEOUS:

- Crew-cab with all manufacturer's standard equipment:
- Truck to feature factory heater/defroster, factory air conditioning,
- AM/FM radio
- Trip odometer
- Clock
- Three (3) man cloth bench seat front and rear
- Cigarette lighter
- Power point in dash
- Day/night rear view mirror
- Fold-in mirrors on left and right sides
- Interior dome light with reading lamps
- Tinted glass all around
- Heavy duty flasher required
- Daytime running lamps
- Floor mats (2)

COLOR:

- Exterior - White
- Interior - Tan

KEYS:

- Three (3) full sets required

MANUALS:

- Complete set of repair manuals, including schematics and body specifications

GENERAL MINIMUM SUGGESTED SPECIFICATIONS
Automobile, Compact, Four (4) Passenger, Four (4) Door
Chevrolet Cobalt, Ford Focus or County Approved Equivalent

G.V.W.:

- N/A

C.A./W.B.:

- 103 in wheel base

ENGINE:

- Minimum four (4) cylinder gasoline with 145 horsepower and 155 ft/lbs torque @ 4000 RPM
- Multi-port fuel injection

COOLING SYSTEM:

- Heaviest available cooling system package with coolant recovery system.
- Cooling system shall be filled with extended life coolant with freeze protection to -30 degrees F, or approved equal.

ALTERNATOR:

- Alternator shall be a 105 AMP minimum
- Battery shall be a minimum of 525 CCA

TRANSMISSION:

- Electronic 4 speed with overdrive
- Transaxle

STEERING:

- Power

BRAKES:

- Power, 4 wheel antilock
- 4 wheel disc brakes

SPRINGS:

- Manufacturer's standard

AXLES:

- Manufacturer's standard

WHEELS AND TIRES:

- 15" steel wheels with 195/60R-15 tires

BODY:

- Standard Four (4) door sedan

FUEL TANK:

- Minimum 12 gallon

WINDSHIELD WIPERS:

- Intermittent with washer

CAB AND MISCELLANEOUS:

- Unit to contain all standard equipment including:
- Factory heater and defroster
- Factory air conditioner
- AM/FM radio
- Interior dome light
- Cigarette lighter
- Tinted glass on rear windows
- Daytime running lamps
- No fleet-delete packages to be applied.
- Trunk or cargo area to contain OEM mat or carpeting
- Cloth upholstery required on all seats
- Fold-in mirrors on left and right sides
- Matching floor mats

COLOR:

- Exterior - white
- Interior - Tan

KEYS:

- Three (3) full sets required

SHOP MANUALS:

- Three full sets of repair and troubleshooting manuals

GENERAL MINIMUM SUGGESTED SPECIFICATIONS

Truck, 1 Ton, Six (6) Passenger P/U 4x2, Crew -Cab Full-Size w/dual rear wheels
Chevrolet C3500, Ford F-350 Super Duty Series, or County Approved Equivalent

G.V.W.:

- 11,400 lb. Minimum
- Towing capacity of 12,000 lbs minimum

C.A./W.B.:

- 167 " wheelbase

ENGINE:

- Diesel V-8 310 horsepower with 605 ft/lbs torque @ 1600 RPM minimum

COOLING SYSTEM:

- Heaviest available cooling system package with coolant recovery system.
- Cooling system shall be filled with extended life coolant with freeze protection to -30 degrees F, or approved equal.

ALTERNATOR:

- Alternator shall be a 105 AMP minimum
- Shall be dual batteries with a minimum of 770 CCA each.

TRANSMISSION:

- 4-speed automatic overdrive w/tow pkg.

STEERING:

- Power

BRAKES:

- Power 4 wheel antilock
- 4 wheel disc brakes

SPRINGS:

- Front - 4,800 lb spring minimum
- Rear - 8,600 lb minimum

AXLES:

- Front: to meet G.V.W.
- Rear: Rear to be limited slip
- 3.73 gear ratio

WHEELS/TIRES:

- Seven (7) matching tires LT-215/85Rx16, tubeless radials, with highway tread appropriate for GVW rating.
- 16 x 6.5 steel wheels, dual rear wheels.

BODY:

- Four (4) door with 8 ft. fleetside bed with double wall construction.
- Bedliner

BUMPERS:

- Standard front bumper with tow hooks mounted on frame.
- Heavy duty rear step bumper with receiver style hitch frame mounted with combo pintle & 2" ball 6 pole female trailer plug
 - Model Pollock #11-609 or approved equal

FUEL TANK:

- 30-gallon minimum capacity. The fuel tank(s) must not interfere with the storage capacity of the truck bed and have a protective shield.

WINDSHIELD WIPERS:

- Intermittent electric

CAB AND MISCELLANEOUS:

- 4 door crew-cab with all manufacturer's standard equipment:
- Truck to feature factory heater/defroster, factory air conditioning,
- AM/FM radio
- Trip odometer
- Clock
- Three (3) man cloth bench seat front and rear
- Cigarette lighter
- Power point in dash
- Day/night rear view mirror
- Fold-in mirrors on left and right sides
- Interior dome light with reading lamps
- Tinted glass all around
- Heavy duty flasher required
- Daytime running lamps
- Floor mats (2)

COLOR:

- Exterior - White
- Interior - Tan

KEYS:

- Three (3) full sets required

SHOP MANUALS:

- Three full sets of repair and troubleshooting manuals

GENERAL MINIMUM SUGGESTED SPECIFICATIONS

Van, Cargo, 1/2 Ton, Gasoline, 2 Passenger 4x2

GMC Savana 1500, Ford E150, Chevrolet Express 1500 or County Approved Equivalent

G.V.W.:

- 7,200 lb. Minimum

C.A./W.B.:

- 135 in. wheelbase

ENGINE:

- Minimum V-8 gasoline with 275 h.p. and 290 ft./lbs torque @ 4,000 RPM

COOLING SYSTEM:

- Heaviest available cooling system package with coolant recovery system.
- Cooling system shall be filled with extended life coolant with freeze protection to -30 degrees F, or approved equal.

ALTERNATOR:

- Alternator shall be a 105 AMP minimum
- Battery shall be a minimum of 600 CCA.

TRANSMISSION:

- 4 speed automatic, electronically controlled with overdrive.

STEERING:

- Power

BRAKES:

- Power 4 wheel antilock
- 4 wheel disc brakes

SPRINGS:

- Front - independent coil springs and stabilizer bar
- Rear - rear multi-leaf springs to meet GVW

AXLES:

- Front: To meet G.V.W.
- Rear: To be limited slip
- 3.73 ratio

WHEELS & TIRES:

- Five (5) 16" x 6.5" 6-lug steel, painted, includes painted center caps standard wheels with five (5) matching P235/75R16EL, all-season, blackwall having a highway tread design.
- Spare to be mounted underneath chassis.

BODY:

- Standard cargo van body with dual rear doors and sliding cargo door on the right side.
- Glass in side and rear doors only.
- General service shelving package

BUMPERS:

- Standard front bumper with tow hooks mounted on frame.
- Rear: Recessed step.

CAB & MISCELLANEOUS:

- All manufacturer's standard equipment
- Factory heater/defroster
- Factory air conditioning
- AM/FM radio
- Cigarette lighter
- Fold-in mirrors on right and left side
- Cloth driver and passenger seat with arm rests
- Interior dome lights in cab area and in rear cargo area
- Full headliner
- Daytime running lamps
- All glass in the van is to be tinted
- Floor to have rubber mat full length of cargo area
- Floor mats

COLOR:

- White exterior
- Tan interior

KEYS:

- Three (3) full sets required

SHOP MANUALS:

Three full sets of repair and troubleshooting manuals

GENERAL MINIMUM SUGGESTED SPECIFICATIONS

Van, Cargo, 3/4 Ton, Gasoline, 2 Passenger 4x2

GMC Savana 2500, Ford E250, Chevrolet Express 2500 or County Approved Equivalent

G.V.W.:

- 8,600 lb. Minimum

C.A./W.B.:

- 135 in. wheelbase

ENGINE:

- Minimum V-8 gasoline with 285 h.p. and 295 ft./lbs torque @ 4,000 RPM

COOLING SYSTEM:

- Heaviest available cooling system package with coolant recovery system.
- Cooling system shall be filled with extended life coolant with freeze protection to -30 degrees F, or approved equal.

ALTERNATOR:

- Alternator shall be a 105 AMP minimum
- Battery shall be a minimum of 600 CCA.

TRANSMISSION:

- 4 speed automatic, electronically controlled with overdrive w/ tow pkg.

STEERING:

- Power

BRAKES:

- Power 4 wheel antilock
- 4 wheel disc brakes

SPRINGS:

- Front - independent coil springs and stabilizer bar
- Rear - rear multi-leaf springs to meet GVW

AXLES:

- Front: To meet G.V.W.
- Rear: To be limited slip
- 3.73 ratio

WHEELS & TIRES:

- Five (5) 16" x 6.5" 6-lug steel, painted, includes painted center caps standard wheels with five (5) matching P235/75R16EL, all-season, blackwall having a highway tread design.
- Spare to be mounted underneath chassis.

BODY:

- Standard cargo van body with dual rear doors and sliding cargo door on the right side.
- Glass in side and rear doors only.
- General service shelving package

BUMPERS:

- Standard front bumper with tow hooks mounted on frame.
- Rear: Recessed step.
- Receiver style hitch w/combo pintle & 2" ball
- 6 pole female trailer plug
 - Model Pollock #11-609 or approved equal

CAB & MISCELLANEOUS:

- All manufacturer's standard equipment
- Factory heater/defroster
- Factory air conditioning
- AM/FM radio
- Cigarette lighter
- Fold-in mirrors on right and left side
- Cloth driver and passenger seat with arm rests
- Interior dome lights in cab area and in rear cargo area
- Full headliner
- Daytime running lamps
- All glass in the van is to be tinted
- Floor to have rubber mat full length of cargo area
- Floor mats
- Electronic brake controller

COLOR:

- White exterior
- Tan interior

KEYS:

- Three (3) full sets required

SHOP MANUALS:

- Three full sets of repair and troubleshooting manuals

GENERAL MINIMUM SUGGESTED SPECIFICATIONS

Van, Cargo, 1 Ton, Gasoline, 15 Passenger 4x2

GMC Savana 3500, Ford E350, Chevrolet Express 3500 or County Approved Equivalent

G.V.W.:

- 9,600 lb. Minimum

C.A./W.B.:

- 155 in. wheelbase

ENGINE:

- Minimum V-8 gasoline with 300 h.p. and 360 ft./lbs torque @ 4,000 RPM

COOLING SYSTEM:

- Heaviest available cooling system package with coolant recovery system.
- Cooling system shall be filled with extended life coolant with freeze protection to -30 degrees F, or approved equal.

ALTERNATOR:

- Alternator shall be a 145 AMP minimum
- Battery shall be a minimum of 800 CCA.

TRANSMISSION:

- 4 speed automatic, electronically controlled with overdrive.

STEERING:

- Power

BRAKES:

- Power 4 wheel antilock
- 4 wheel disc brakes

SPRINGS:

- Front - independent coil springs and stabilizer bar
- Rear - rear multi-leaf springs to meet GVW

AXLES:

- Front: To meet G.V.W.
- Rear: To be limited slip
- 3.73 ratio

WHEELS & TIRES:

- Five (5) 16" x 7" 6-lug steel, painted, includes painted center caps standard wheels with five (5) matching P245/75R16E, all-season, blackwall having a highway tread design.
- Spare to be mounted underneath chassis.

BODY:

- 15 Passenger Van (2-3-3-3-4) seating configuration
- Swing out door passenger side
- Swing out door drivers side

BUMPERS:

- Standard front bumper with tow hooks mounted on frame.
- Recessed rear step.

CAB & MISCELLANEOUS:

- All manufacturer's standard equipment
- Factory heater/defroster
- Dual front and rear factory air conditioning
- AM/FM radio
- Cigarette lighter
- Fold-in mirrors on right and left side
- Cloth seats
- Interior dome lights
- Full headliner
- Daytime running lamps
- Floor to have full carpeting
- Deep Tinted windows (all except light tinted glass on windshield, drivers and front passenger)
- Floor mats

COLOR:

- White exterior
- Tan interior

KEYS:

- Three (3) full sets required

SHOP MANUALS:

- Three full sets of repair and troubleshooting manuals

GENERAL MINIMUM SUGGESTED SPECIFICATIONS

Pickup Truck, 3/4 Ton, Full-Size 4x4

Ford F250, GMC Sierra K2500, Chevrolet K2500 or County Approved Equivalent

G.V.W.:

- 9,200 lb. Minimum
- 10,500 lb towing capacity minimum

C.A./W.B.:

- 133 in. wheelbase minimum

ENGINE:

- Minimum V-8 gasoline with 300 HP with 360 ft.lbs torque @ 4,000 RPM

COOLING SYSTEM:

- Heaviest available cooling system package with coolant recovery system.
- Cooling system shall be filled with extended life coolant with freeze protection to -30 degrees F, or approved equal.

ALTERNATOR:

- Alternator shall be a 105 AMP minimum
- Battery shall be a minimum of 600 CCA.

TRANSMISSION:

- Electronically controlled 4-speed automatic overdrive w/tow pkg.
- Factory OEM skid plate package

STEERING:

- Power

BRAKES:

- Power 4 wheel antilock
- 4 wheel disc brakes

SPRINGS:

- Front: 4,500 lbs minimum
- Rear: 6,000 lbs minimum

AXLES:

- Designed to meet G.V.W.
- Front to have automatic locking hubs
- Rear axle to be of limited slip design
- 3.73 ratio

WHEELS/TIRES:

- Five (5) 16" x6.5" 6-lug steel, painted, includes painted center caps standard wheels with five (5) matching P245/75R16E, on/off road, blackwall
- Spare to be mounted inside or underneath chassis.

BODY:

- 8 ft. fleetside bed with double wall construction.

BUMPERS:

- Standard front bumper with tow hooks mounted on frame.
- Recessed step bumper on rear
- Receiver style hitch w/combo pintle & 2" ball
- 6 pole female trailer plug
 - Model Polock #11-609 or approved equal

FUEL TANK:

- Standard dual tanks, or 30-gallon minimum single tank.

WINDSHIELD WIPERS:

- Intermittent

CAB & MISCELLANEOUS:

- Standard cab with all manufacturer's standard equipment
- Factory air conditioning,
- Factory heater and defroster
- Tinted glass
- Cloth bench seat
- AM/FM radio
- Fold-in mirrors on right and left side
- Inside day/night rear view mirror
- Power point in dash
- Interior dome light.
- Daytime running lamps
- Floor mats
- Electronic brake controller

KEYS:

- Three (3) full sets required

COLOR:

- Exterior - White
- Interior - tan

SHOP MANUALS:

- Three full sets of repair and troubleshooting manuals

GENERAL MINIMUM SUGGESTED SPECIFICATIONS

Pickup Truck, 1/2 Ton, Full-Size 4x4

Ford F150, GMC Sierra K1500, Chevrolet K1500 or County Approved Equivalent

G.V.W.:

- 6,400 lb. Minimum
- 8,100 lb towing capacity

C.A./W.B.:

- 133 in. wheelbase minimum

ENGINE:

- Minimum V-8 cylinder gasoline with 285 HP and 295 ft./lbs torque @ 4,000 RPM

COOLING SYSTEM:

- Heaviest available cooling system package with coolant recovery system.
- Cooling system shall be filled with extended life coolant with freeze protection to -30 degrees F, or approved equal.

ALTERNATOR:

- Alternator shall be a 145 AMP
- Battery shall be a minimum of 600 CCA.

TRANSMISSION:

- Electronically controlled 4-speed automatic overdrive w/tow pkg.
- Electronic transfer case with push-button controls
- Factory OEM skid plate package.

STEERING:

- Power

BRAKES:

- Power 4 wheel antilock
- 4 wheel disc brakes

SPRINGS:

- Front: 3,925 lbs minimum
- Rear: 3,750 lbs minimum

AXLES:

- Designed to meet G.V.W.
- Rear axle to be of limited slip design
- 3.73 ratio

WHEELS/TIRES:

- Five (5) 17" x 7" 6-lug steel, painted, includes painted center caps standard wheels with five (5) matching P265/70R17, all-season, blackwall having an on road/off road tread design.
- Spare to be mounted inside or underneath chassis.

BODY:

- 8 ft. fleetside bed with double wall construction.
- Bedliner

BUMPERS:

- Standard front bumper with tow hooks mounted on frame.
- Heavy duty rear step bumper with receiver style hitch frame mounted with combo pintle & 2" ball
- 6 pole female trailer plug
 - Model Polock #11-609 or approved equal

FUEL TANK:

- 30-gallon minimum single tank.

WINDSHIELD WIPERS:

- Intermittent

CAB & MISCELLANEOUS:

- Standard cab with all manufacturer's standard equipment
- Factory air conditioning,
- Factory heater and defroster
- Tinted glass
- Cloth bench seat
- AM/FM radio
- Fold-in mirrors right & left side
- Inside day/night rear view mirror
- Cigarette lighter
- Power point in dash
- Interior dome light.
- Daytime running lamps
- Floor mats
- Electronic Brake controller

KEYS:

- Three (3) full sets required

COLOR:

- White exterior
- Tan interior

SHOP MANUALS:

- Three full sets of repair and troubleshooting manuals